











		1	2	3	4	5	6	7	8	9	10	
画像												
製品	単位	JSW0508	JUL0810	JUM2400N	JUM2452PO	JUD2458PO	JUM3041PO	JUH3442PO	JSW0760PO-T (JUW0760T)	JSW0510G	JUD2457PO_STD	
用途	-	地デジ	RF-ID EU/JAP/USA	CDMA	Blue Tooth Wi-Fi/ZigBee	Wi-Fi/Wi-MAX 2400/5200	LTE ADV	ローカル5G 3600~4200	テーブルANT	<10GHz対応> 無指向性ANT	Wi-Fi 無指向性ANT	
周波数帯域	MHz	470~1000	820~980	2250~2800	2250-2600/5200-5600	2300-2600/5700-5900	3000~4200	3400~4400	700~6000	470~10,000M/15G	2450~5900	
インピーダンス	Ω	50	50	50	50	50	50	50	50	50	50	
偏波面	-	Linear	Linear	Linear	Linear	Linear	Linear	Linear	Linear	V:垂直	V:垂直	
指向性	-	無指向性	無指向性	無指向性	無指向性	無指向性	無指向性	無指向性	無指向性	無指向性	無指向性	
指向性利得	dBi	≧+9.0	≧+3.0	≧+3.0	≧+3.0	≧+3.0	≧+3.0	≧+3.0	≧+3.0	≧+3.0	≧+5	
VSWR	-	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	
標準コネクタ	-	SMA-P(NP)/F	U_FL/I-PEX/SMA	U_FL/I-PEX/SMA	U_FL/I-PEX/SMA	U_FL/I-PEX/SMA	U_FL/I-PEX/SMA	U_FL/I-PEX/SMA	SMA-J/I-PEX	SMA-J	SMA-J/I-PEX	
耐久温度	°C	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	
耐久湿度	%	10-85	10-85	10-85	10-85	10-85	10-85	10-85	10-85	10-85	10-85	
		(-5°Cで結露なきこと)										
全長(除con)	mm	195 x 115 x 1	130 x 70 x 1	10 x 70 x 1	10 x 70 x 1	10 x 70 x 1	10 x 70 x 1	10 x 50 x 1	60x125x6	1x160x160	25x60x1	
材質		FR-4	FR-4/FPC	FR-4	FR-4	FR-4	FR-4	FR-4	FR-4	FR-4	FR-4	
重量	g	61	6	1	1	1	1	1	100	320	5	

		11	12	13	14	15	16	17	18	19	20	
画像												
製品	単位	JSL0920CPD	JSL0822PD _2EL45	JSL0920D_YU	JSM2400PDW-7 ※2EL,5ELなど	JSM2400PDW-7 双方向ANT (中継局)	JUH5758-7D	JUH3643CP	JSW0410PD_STDLog	JSW0318PD-230 Wing	JSW0318PD-230 Gun	
用途	-	特定小電力用 RF-ID	携帯電話基地局対応 ドローン用2EL	<920MHz対応>	Blue Tooth Wi-Fi/ZigBee	Wi-Fi/Bluetooth 双方向アンテナ (中継局ANT)	ローカル5G (6G対応) 円偏波ANT	ローカル5G (or 6G対応) 円偏波ANT4 x 4	<10GHz対応> Log·pely	<18GHz対応>	<18GHz対応>	
周波数帯域	MHz	880~1000	815/1750/2170	820~960	2300~2500	2200~2700	5700~5900	3000~4600	330~10,000	450~18,000	450~18,000	
インピーダンス	Ω	50	50	50	50	50	50	50	50	50	50	
偏波面	-	Circularly	Linear	V:垂直	Linear	Linear	Circularly	Circularly	V:垂直	V:垂直	V:垂直	
指向性	-	指向性	指向性	指向性	指向性	指向性	指向性	指向性	指向性	指向性	指向性	
指向性利得	dBi	≧+9.0	≧+6.0	≧+7.0	≧+7.0	≧+6.0	≧+10	≧+10	≧+7.0	≧+3.0	≧+3.0	
VSWR	-	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	≦2.0	
標準コネクタ	-	SMA(J)	I-PEX/SMA	SMA-J	SMA-J	SMA-J	SMA-J	SMA-J	SMA-J	SMA-J	SMA-J	
耐久温度	°C	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	-20~+60	
耐久湿度	%	10-85	10-85	10-85	10-85	10-85	10-85	10-85	10-85	10-85	10-85	
		(-5°Cで結露なきこと)										
サイズ	mm	180 x 180 x 30	60 x 70 x 1	365 x 230 x 30	75 x 75 x 1	300 x 70 x 1	100 x 100 x 80	120 x 170 x 10	330 x 300 x 1	260 x 230 x 100	365 x 230 x 30	
材質		FR-4	FR-4	アルミ	FR-4	FR-4	FR-4	FR-4	FR-4	FR-4	FR-4	
重量	g	310	31	330	12	30	150	130	350	400	300	